

Cold Glue

# UZIN RK 33

Dispersion-based cold glue (D3) for gluing tongue and groove wooden floors

**MAIN APPLICATION FIELD:**

- ▶ engineered wood flooring
- ▶ chipboard
- ▶ OSB boards

**PRODUCT BENEFITS/FEATURES:**

UZIN RK 33 is a viscous, water-based dispersion, bottled white glue for tongue and groove wooden flooring. Can also be used as a universal wood glue for joints, pins, plugs or similar. For interior use.

- ▶ very quick and transparent drying
- ▶ good water resistance
- ▶ stress group D3

**TECHNICAL DATA:**

Packaging	plastic bottle with nozzle
Pack size	810 g
Shelf life	min. 12 months
Color	white
Consumption	5 - 30 g / linear metre, depending on joint size
Working time	5 - 10 minutes*
Minimum application temperature	15 °C at ground level
Loadable	after approx. 12 hours*
Grindable	after 1 - 2 days*

\*At 20 °C and 65% relative humidity.

**EXTENDED APPLICATIONS:**

- ▶ laminate floors
- ▶ universal wood glue

**APPLICATION:**

1. Cut off the tip of the nozzle at an angle according to the required size.
2. Apply glue to the tongue or into the groove. Then join the wood elements within the working time and fix together, if necessary use a tapping block or hammer.
3. A small amount of glue escapes if fitted correctly.
4. Completely remove escaping glue with a moist cloth.

**CONSUMPTION:**

Consumption (depending on joint size)	5 - 30 g / linear metre
Bottle is sufficient for	25 - 150 linear metres

Consumption: At 20 °C and 65% relative humidity, with tempered adhesive bottles.

**IMPORTANT NOTES:**

- ▶ A shelf life of 12 months when stored in moderately cool conditions, in the original packaging. Frost-resistant down to - 25 °C. Carefully and tightly reseal opened containers and use the contents quickly. Allow containers to come to room temperature before use.
- ▶ Best applied between 18 - 25 °C, with the floor temperature above 15 °C and relative air humidity below 65%.

**SEALS OF QUALITY & ECOLABELS:**

- ▶ Solvent-free

**COMPOSITION:**

Polymer dispersion, additives and water.

**PROTECTION OF THE WORKPLACE AND THE ENVIRONMENT:**

Solvent-free. Use of barrier cream and ventilation of the work area are recommended. When fully dried, has a neutral odour and presents no physiological or ecological risk. Basic prerequisites for best possible indoor air quality following floor covering work are conformity to standards of the working conditions, as well as thoroughly dry substrate, primer and smoothing compound.

**DISPOSAL:**

Where possible, collect product residues and re-use. Do not allow dispersal into drains, sewers or ground. Empty, scraped and drip-free containers are recyclable. Containers with liquid residue, as well as the liquid product, are classed as Special Waste. Dried product residues are classed as Construction Waste.